

LTC 5231/90 and LTC 5234/90

Video Distribution Amplifiers



Security Systems

- Compatible with NTSC/PAL Video Standards
- No User Adjustments Needed
- Supports Bilinx Video Signals
- Video Presence Indicators
- Video-Loss-Detection Output
- Optional Rack-mounting



The LTC 5231/90 and LTC 5234/90 are video distribution amplifiers that provide multiple video outputs identical to the video input signal. Their ample bandwidth easily supports today's high-resolution video signals. A video-loss-detection feature is available for interfacing to external monitoring equipment.

The LTC 5231/90 and LTC 5234/90 also support Bilinx technology, allowing bidirectional communication through the video cable to access and control Bilinx-enabled devices such as AutoDome and Dinion cameras. A maximum of two (2) different types of Bilinx controller models can communicate to a common Bilinx-capable camera. Check with Bosch Security Systems Sales Representative regarding future product capabilities.

The LTC 5231/90 is a single-channel video distribution amplifier with four (4) video outputs for distribution to other video devices. A front panel LED indicates the presence of video.

The LTC 5234/90 is a 4-channel video distribution amplifier. It has four (4) independent distribution amplifiers, each with one input and three outputs. Front panel LEDs for each distribution amplifier channel indicates the presence of video.

These are indoor products and supplied as desktop units. Rack-mount kits are available from Bosch Security Systems for mounting in a standard EIA 19-inch rack.

LTC 5231/90: Single-Channel

Electrical

Model Number	LTC 5231/90
Rated Voltage	120/230 VAC, 50/60 Hz
Voltage Range	108 to 264
Power at Rated Voltage	3.5 W
Video Inputs	One (1), fixed 75 Ω termination
Signal Range	0.7 Vp-p to 1.4 Vp-p
Video Outputs	Four (4) Isolated, 75 Ω
Video Gain	Unity +1.0/-0%
Signal-to-noise	-72 dB Typical
Bandwidth -3 dB Point	33 MHz Typical
Differential Gain	0.7% Typical
Differential Phase	0.8° Typical
Field Time Distortion	2.9%
Video-loss Output	Relay contact pair Rating: 1 A at 40 volts AC/DC maximum
Indicators	Power on LED (green) Video presence LED (green)

Mechanical

Construction	Steel chassis with sheet metal cover and plastic bezel
Finish	Charcoal
Size (H x W x D)	4.1 x 23.4 x 26.2 cm (1.6 x 8.8 x 10.3 in.)
Weight	Approximately 1.5 kg (3.4 lb)

Environmental

Operating Temperature	0°C to 50°C (32°F to 122°F)
Humidity	20% to 90% relative, noncondensing

Product Regulatory Compliance

Electromagnetic Compatibility (EMC)	Complies with FCC Part 15, ICES-003 and CE regulations
Product Safety	Complies with CE regulations, UL, CSA, EN and IEC Standards

Options

EIA 19-inch rack kit	LTC 9101/00
	Height: 1 Standard rack unit
	Width: 1 Standard rack unit

LTC 5234/90: 4-Channel

Electrical

Model Number	LTC 5234/90
Rated Voltage	120/230 VAC, 50/60 Hz
Voltage Range	108 to 264
Power at Rated Voltage	5.5 W
Video Inputs	Four (4), fixed 75 Ω termination
Signal Range	0.7 Vp-p to 1.4 Vp-p
Video Outputs	Three (3) for each channel, 75 Ω
Video Gain	Unity +1.0/-0%
Signal-to-noise	-72 dB Typical
Bandwidth -3 dB Point	33 MHz Typical
Differential Gain	0.6% Typical
Differential Phase	0.6° Typical
Field Time Distortion	2.2%
Video-loss Output	Relay contact pair for each channel Rating: 1 A at 40 volts AC/DC maximum
Indicators	Power on LED (green) Four (4) Video presence LEDs (green)

Mechanical

Construction	Steel chassis with sheet metal cover and plastic bezel
Finish	Charcoal
Size (H x W x D)	4.1 x 23.4 x 26.2 cm (1.6 x 8.8 x 10.3 in.)
Weight	Approximately 1.6 kg (3.6 lb)

Environmental

Operating Temperature	0°C to 50°C (32°F to 122°F)
Humidity	20% to 90% relative, noncondensing

Product Regulatory Compliance

Electromagnetic Compatibility (EMC)	Complies with FCC Part 15, ICES-003 and CE regulations
Product Safety	Complies with CE regulations, UL, CSA, EN and IEC Standards

Options

EIA 19-inch rack kit	LTC 9101/00
	Height: 1 Standard rack unit
	Width: 1 Standard rack unit

Bilinix, AutoDome, and Dinion are registered by Bosch Security Systems, Inc. in the US patent trademark office.

Americas

Bosch Security Systems
130 Perinton Parkway
Fairport, New York, 14450, USA
Phone: +1 (585) 223 4060
+1 800 289 0096
security.sales@us.bosch.com
http://www.boschsecurity.us

Europe, Middle East, Africa

Bosch Security Systems B.V.
P.O. Box 80002
5600 JB Eindhoven, The Netherlands
Phone: +31 (0) 40 27 83955
Fax: +31 (0) 40 27 86668
ema.securitysystems@bosch.com
http://www.boschsecurity.com

Asia-Pacific

Bosch Security Systems Pte Ltd
38C Jalan Pemimpin
Singapore 577180
Phone: +65 6319 3450
Fax: +65 6319 3499
apr.securitysystems@bosch.com
http://www.boschsecurity.com

BOSCH